

High protection against burglary



# **MAGNA - CLASS BB**

## **BURGLARY RESISTANCE SAFES**

#### **KEY FEATURES**

- High-security safes for protection of cash and valuables certified as per IS 550-Class BB by the Bureau of Indian Standards.
- Customers can select from a wide range of sizes, starting from 90 to 325 litres.
- Specially formulated barrier material for resistance from torch and tool attacks.
- Choose from a wide range of lock options like combination, electronic, or biometric access control systems.
- Ideal for high-risk business environments, banks, high-end retailers, jewellers or pawnshops for storing cash and valuables.

PAN INDIA SERVICE AND INSTALLATION NETWORK

Class	Model	External Height (mm)	External Width (mm)	External Depth (mm)	Internal Height (mm)	Internal Width (mm)	Internal Depth (mm)	Capacity (litres)	Net Weight (kg)	No. of Drawers	No. of Shelves
BB	90	790	740	658	550	500	330	90	820	2	1
BB	140	1090	740	658	850	500	330	140	1220	2	1
BB	260	1280	740	828	1040	500	500	260	1600	2	2
BB	325	1540	740	828	1300	500	500	325	1950	2	2

Standard door is right hung. Gunnebo policy is one of constant improvement. We reserve the right to alter specifications without prior notice.

#### **LOCK OPTIONS**



Combination lock



Electronic lock



Biometric access control system

### **PRODUCT BENEFITS**

- Monolithic door construction for superior strength.
- Continuous rebate on the hinge side for enhanced protection.
- Gold storage options like drawers and trays.
- Option of Non-retractable key for drawers.
- Choice of 4 models 90 to 325 litres.
- Option of combination lock and biometric access control system for enhanced security.
- Option of Left Hung (LH) door.

Gunnebo India Pvt. Ltd
Unit No 102, 1st Floor, Akruti SMC Building,
LBS Rd, Khopat, Thane West-400601, Maharashtra, India
Tel. +022 6780 3500 Fax: +91 2267803535
For service enquiry call Toll Free: 1800 22 3525, 1800 209 3040,
or email us at customercare.india@gunnebo.com

www.steelage.com

<sup>\*</sup>Tolerance on weight +/- 10% & Tolerance on dimensions is +/- 5 mm

<sup>\*</sup>Conditions Apply